


Indoor light

# RS PRO 5800 LED

Slave

EAN 4007841 007669

**STEINEL**  
PROFESSIONAL



**LED**

**33w**



4000K neutral white



high frequency sensor 360°



Ø 2 - 8 m

**IP66**

IP66 Dust-proof and jet water protected



soft light start



10 - 50% basic brightness



shock proof IK07



networkable via cable

## Function description

Dynamic lighting intelligence. RS PRO 5800 LED high-frequency SensorLight, ideal for corridors, thoroughfares and stairwells as well as WC facilities, washrooms and warehouses or multi-storey car parks and cold rooms. 33 W for 4065 lm of light, optional 10% – 50 % basic light level, integrated DALI interconnection capability, swarm function for dynamic light, RGS – Remote Group Setting function, lighting groups, including basic light level, can be synchronised, adjustment by optional RC 10 remote control.

## Technical specifications

Dimensions (L x W x H)	1278 x 105 x 105 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Output	33 W
Luminous flux	4065 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	No

Photo-cell controller	No
Time setting	5 s – 15 Min.
Functions	Group parameterisation, Neighbouring-light function, Presence function
Soft light start	Yes
Impact resistance	IK07
IP rating	IP66
Protection class	I
Ambient temperature	-20 – 30 °C
Housing material	Plastic
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
Version	Slave
PU1, EAN	4007841007669

## Accessories

EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 008925	RC10 for RS PRO 5800/5850 LED

Indoor light

# RS PRO 5800 LED

Slave

EAN 4007841 007669

**STEINEL**<sup>®</sup>  
PROFESSIONAL

## Dimension Drawing

