


Indoor light

RS PRO 5850 LED

Slave

EAN 4007841 007683

STEINEL
PROFESSIONAL



LED

45w



4000K neutral white



high frequency sensor 360°



Ø 2 - 8 m

IP66

IP66 Dust-proof and jet water protected



soft light start



10 - 50% basic brightness



shock proof IK07



networkable via cable

Function description

Dynamic lighting intelligence. RS PRO 5850 LED Slave high-frequency SensorLight, ideal for corridors, thoroughfares and stairwells as well as WC facilities, washrooms and warehouses or multi-storey car parks and cold rooms. 45 W for 5570 lm of light, optional 10 – 50 % basic light level, without sensor.

Technical specifications

Dimensions (L x W x H)	1583 x 105 x 105 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Transmitter power	< 1 mW
Output	45 W
Luminous flux	5570 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	No

Photo-cell controller	No
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 Min.
Functions	Group parameterisation, Neighbouring-light function, Presence function
Soft light start	Yes
Impact resistance	IK07
IP rating	IP66
Protection class	I
Ambient temperature	-20 – 30 °C
Housing material	Plastic
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
Version	Slave
PU1, EAN	4007841007683

Accessories

EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 008925	RC10 for RS PRO 5800/5850 LED

<https://www.steinell.de>

Indoor light

RS PRO 5850 LED

Slave

EAN 4007841 007683

STEINEL[®]
PROFESSIONAL

Dimension Drawing

