
Stainless steel EAN 4007841 010454









**7,5**w

















# **Function description**

Light with informative value. Modern L 220 LED sensor-switched outdoor light with large, square front surface for self-adhesive house numbers. Inviting, soft ambient light for entrances. Light output of  $550 \, \text{lm}$  at a power consumption of only  $7.5 \, \text{W}$ .  $180^{\circ}$  angle of coverage,  $10 \, \text{m}$  reach.

## **Technical specifications**

Dimensions (L x W x H)	251 x 246 x 84 mm
	201 X 2 10 X 0 1 11111
Mains power supply	220 – 240 V / 50 – 60 Hz
Mounting height max.	3,00 m
Sensor Technology	passive infrared
Output	7,5 W
Interconnection	No
Luminous flux	550 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordar with LM80	nce L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection angle	180 °
Sneak-by guard	Yes


Capability of masking out individual segments	Yes
Electronic scalability	No
Mechanical scalability	No
Reach, radial	$r = 3 \text{ m } (14 \text{ m}^2)$
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	60 s – 15 Min.
Impact resistance	IK07
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 50 °C
Housing material	Stainless steel
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
includes sheet of self-adhesive numbers	Yes
Settings via	Potentiometers
Version	Stainless steel
PU1, EAN	4007841010454

# Sensor-switched outdoor light

Stainless steel EAN 4007841 010454



### **Detection Zone**



Mögliche Montagehöhe: 1,80 m – 3,00 m Orange: radial Schwarz: tangential

# **Dimension Drawing**

