


Sensor-switched indoor light

RS PRO LED S2

V4 PC neutral white

EAN 4007841 035808

STEINEL[®]
PROFESSIONAL



LED

30 years (Ø 4,5h / day)



4000K neutral white



high frequency sensor 360°



1 - 8 m



2 - 2000 lux



5 sec - 15 min



networkable wireless



energy saving



manufacturer's warranty
steinel-professional.de/garantie



CE

Function description

The smartest light in the world. High-frequency sensor-switched light RS PRO LED S2, ideal for office corridors, passageways, WC facilities, stairwells, can be wirelessly interconnected with RS PRO LED S1 and S2, 26 W LED/2210 lm, polycarbonate shade, 4000 K, 360° detection, reach 1 – 8 m, basic light-level function, presence mode and neighbouring light function.

Sensor-switched indoor light

RS PRO LED S2

V4 PC neutral white

EAN 4007841 035808



Technical specifications

Dimensions (Ø x H)	350 x 83 mm
Mains power supply	230 – 240 V / 50 – 60 Hz
Sensor Technology	High frequency
Transmitter power	< 1 mW
Output	26 W
Interconnection	Yes
Luminous flux	2210 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	70000 h
Drop in luminous flux in accordance with LM80	L80B10
Base	Other
LED cooling system	Active Thermo Control
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °
Electronic scalability	Yes

Mechanical scalability	No
Reach, radial	Ø 8 m (50 m²)
Continuous light	selectable, 4h
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 Min.
Basic light level function	Yes
Basic light level function time	all night, 10/30 min
Functions	Neighbouring-group function, Presence function
Soft light start	Yes
Impact resistance	IK07
IP-rating	IP20
Protection class	II
Ambient temperature	-10 – 50 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
Settings via	DIP switches, Potentiometers, Remote control, Smart Remote
Version	PC neutral white
PU1, EAN	4007841035808

Accessories

EAN 4007841 009151 Remote control Smart Remote

Sensor-switched indoor light


RS PRO LED S2

V4 PC neutral white

EAN 4007841 035808

STEINEL[®]
PROFESSIONAL


Detection Zone




Mögliche Montagehöhe: 2,00 m – 4,00 m

Orange: radial und tangential

Dimension Drawing




Light Distribution Curve



Output	26 W
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
Luminous flux	2210 lm
Colour temperature	4000 K
Colour Rendering Index CRI	80-89
LED life expectancy (max. °C)	70000 h
LED cooling system	Active Thermo Control

Slave/wireless master interconnection circuit diagram



Sensor-switched indoor light

RS PRO LED S2

V4 PC neutral white

EAN 4007841 035808

STEINEL[®]
PROFESSIONAL

Master/master interconnection circuit diagram

