Sensor-switched indoor light











## **Function description**

Make elegant statements. Translucent RS LED M2 indoor LED lights for ceiling and wall. With an impressive 873 lm for classy ambient light at a power consumption of just 9,5 W. Integrated high-frequency sensor with an angle of coverage of 360° and reach of up to ø 6 m. Night-light function and 4-hour manual override (3000 K). Available in either chrome or silver.

## **Technical specifications**

Dimensions (L x W x H)	220 x 220 x 67 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	High frequency
Transmitter power	< 1 mW
Output	9,5 W
Interconnection	Yes
Luminous flux	873 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	65000 h
Drop in luminous flux in accordar with LM80	<sup>ICE</sup> L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °

Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	Ø 8 m (50 m²)
Reach, tangential	Ø 8 m (50 m²)
Continuous light	selectable, 4h
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 Min.
Basic light level function	Yes
Basic light level function time	10/30 min, all night
Soft light start	Yes
Impact resistance	IK00
IP rating	IP20
Protection class	II
Ambient temperature	-10 – 30 °C
Housing material	Plastic
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
Version	Silver
PU1, EAN	4007841052515

## https://www.steinel.de

Sensor-switched indoor light





## **Detection Zone**



Mögliche Montagehöhe: 2,00 m – 4,00 m Orange: radial und tangential **Dimension Drawing** 

