
Sensor-switched outdoor light

DL Vario Quattro PRO LED

warm white anthracite
EAN 4007841 057596





LED	14w								
30 years (Ø 4,5h / day)	14 W 1430 lm	3000K warm-white	Infrared sensor ideal 12 x 12 m	Scalable in every direction	IP54	2 - 1000 lux	5 sec - 30 min	soft light start	manual override

Function description

Detects precisely where you want it to. No more irritating inadvertent triggering. Four precision infrared sensors guarantee 360° all-round detection and can be adjusted in four directions to accommodate any situation. This makes it possible to define the detection zone with absolute precision. Reach: 2 to 8 m. Clean look without sensor elements to spoil the design because the sensor lenses are integrated into the luminaire diffuser where they are virtually hidden from view – a patented world first! 1430 lm at 14 W. In neutral white or warm white.

Sensor-switched outdoor light

DL Vario Quattro PRO LED


warm white anthracite
EAN 4007841 057596

Technical specifications

Mains power supply	220 – 240 V / 50 – 60 Hz
Mounting height max.	6,00 m
Sensor Technology	passive infrared
Output	14 W
Interconnection	Yes
Luminous flux	1430 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	No
Mechanical scalability	Yes


Reach, detail	Reach adjustable from 2 - 8 m in 4 directions (90° in each)
Reach, radial	4 x 4 m (16 m²)
Photo-cell controller	Yes
Twilight setting	2 – 1000 lx
Time setting	5 sec – 30 min
Basic light level function	Yes
Basic light level function time	10/30 min, all night
Soft light start	Yes
Continuous light	selectable, 4h
Impact resistance	IK07
IP-rating	IP54
Protection class	II
Ambient temperature	-20 – 35 °C
Housing material	Plastic
Cover material	Plastic, structured
Manufacturer's Warranty	5 years
Settings via	Potentiometers
With remote control	No
Version	warm white anthracite
PU1, EAN	4007841057596

Detection Zone



Mögliche Montagehöhe: 2,00 m – 6,00 m
Orange: radial
Schwarz: tangential
4 skalierbare Zonen

Dimension Drawing




Sensor-switched outdoor light

DL Vario Quattro PRO LED

warm white anthracite


EAN 4007841 057596

Light Distribution Curve



Output	14 W
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
Luminous flux	1430 lm
Colour temperature	3000 K
Colour Rendering Index CRI	80-89
LED life expectancy (max. °C)	50000 h
LED cooling system	Passive Thermo Control

Master circuit diagram



Master/master interconnection circuit diagram

