


Indoor light

RS PRO DL LED 20 W

EAN 4007841007775



Functional description

The RS PRO LED DL 20 W is the more powerful version of the LED downlighter. And there's not much left to see from this indoor ceiling light with high-frequency sensor either. Once in place, the entire system fits flush with the suspended ceiling, with the easy-fit clamp-type retainer making installation a breeze. Incidentally, the energy efficiency of the RS PRO DL LED 20W can be increased even further by using interconnectable slave versions.

Technical specifications

Dimensions (Ø x H)	168 x 88 mm
Mains power supply	100 – 240 V , 50 / 60 Hz
Transmitter power	< 1 mW
Output	20 W
Output, detail	Only via Eltako ER12DX-UC
Luminous flux	1077 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	No
Photo-cell controller	No
Time setting	60 s – 60 min
Basic light level function time	10 min, 30 min, all night
Impact resistance	IK00
IP rating	IP20
Protection class	II
Ambient temperature	-10 – 40 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
Version	Slave - warm white

Indoor light

RS PRO DL LED 20 W

EAN 4007841007775

Light distribution curve 1

