NVC Lighting Limited
NVC Park 201, Hollymoor Way, Rubery, Birmingham, B31 5HE
UK **T** +44 (0)121 457 6340 **F** +44 (0)121 453 1325
E sales@nvcuk.com

DATA SHEET

BURBANK

Burbank 6W LED Gimbal Downlighter 940

Mains Dimmable LED Recessed Downlighter
Head Tilt Action
Easy Installation

GENERAL INFORMATION	
Product Code	NBU6/G/940
Product Range	Burbank
Product Category	Downlights
Fixing Method	Recessed
IP Rating	44 to front
IK Rating	N/A
Warranty	5 Years Unlimited Hours
DIMENSION/WEIGHT	
Dimensions (D x DIA) (mm)	D=44, DIA=96
Cut-out Size (mm)	78-83
Product Weight (Kg)	0.3
CONSTRUCTION	
Body Material	Die Cast Aluminium
Body Colour	White RAL9003
Optical Material	Acrylic
Optical Finish	Clear
Termination	3x2x2.5mm sq. Push In Terminal
Driver - Integral or Remote	Remote
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A





LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	630
Power Consumption (W)	6
Efficacy (l.lm/c.W)	105
Operating Temp. (Min/Max)	-20°C - 25 °C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Colour Rendering Index (CRI)	>90
Lumen Depreciation	L70 100000
SDCM	<3
ELECTRICAL INPUT	
Voltage (V)	220-240V AC
Operating Frequency	50
In Rush	N/A
Drivers per MCB*	N/A
Class	Class 2
Power Factor	>0.95
Cable Entry	On Driver
ELECTRICAL OUTPUT	
Forward Current (mA)	140mA
Forward Voltage (Vf)	30-40V DC
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	N/A
OTHER	Mains Dimmable
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN Number	5055943084797

* GUIDE ONLY