

Stainless steel EAN 4007841 007140 Article number 007140







## **Function description**

The future of illuminated house numbers. Sensor-switched LED light XSolar LH-N, ideal for entrance areas and building frontages. Automatic light at dusk, mains-free illuminated house number, lithium-iron phosphate rechargeable battery for 365 days of light a year, including adhesive house numbers.



Stainless steel EAN 4007841 007140 Article number 007140



## **Technical specifications**

| Dimensions (L x W x H)                                                                                                | 50 x 242 x 227 mm                          |
|-----------------------------------------------------------------------------------------------------------------------|--------------------------------------------|
| With lamp                                                                                                             | Yes, STEINEL LED system                    |
| With motion detector                                                                                                  | No                                         |
| Manufacturer's Warranty                                                                                               | 3 years                                    |
| Settings via                                                                                                          | Potentiometers                             |
| Version                                                                                                               | Stainless steel                            |
| PU1, EAN                                                                                                              | 4007841007140                              |
| Application, place                                                                                                    | Outdoors                                   |
| Application, room                                                                                                     | outdoors, front door, courtyard & driveway |
|                                                                                                                       |                                            |
| Colour                                                                                                                | Stainless steel                            |
| Colour<br>includes sheet of self-adhesive<br>numbers                                                                  | Stainless steel<br>Yes                     |
| includes sheet of self-adhesive                                                                                       |                                            |
| includes sheet of self-adhesive<br>numbers                                                                            | Yes                                        |
| includes sheet of self-adhesive<br>numbers<br>Installation site                                                       | Yes wall                                   |
| includes sheet of self-adhesive<br>numbers<br>Installation site<br>Impact resistance                                  | Yes<br>wall<br>IK03                        |
| includes sheet of self-adhesive<br>numbers<br>Installation site<br>Impact resistance<br>IP-rating                     | Yes<br>wall<br>IK03<br>IP44                |
| includes sheet of self-adhesive<br>numbers<br>Installation site<br>Impact resistance<br>IP-rating<br>Protection class | Yes<br>wall<br>IK03<br>IP44<br>III         |

| Photo-cell controller Yes                            |  |
|------------------------------------------------------|--|
|                                                      |  |
| Colour temperature 4000 K                            |  |
| Colour variation LED SDCM5                           |  |
| Colour Rendering Index 80-89                         |  |
| Lamp LED cannot be replaced                          |  |
| LED life expectancy (max. °C) 50000 h                |  |
| Drop in luminous flux in accordance L70B10 with LM80 |  |
| LED cooling system Passive Thermo Control            |  |
| Soft light start No                                  |  |
| Functions Light sensor                               |  |
| Twilight setting 2 lx                                |  |
| Basic light level function Yes                       |  |
| Basic light level function time all night            |  |
| Output 0,03 W                                        |  |
| Akku-Ladung ab 0°                                    |  |
| Akku-Funktion ab - 20                                |  |

## **Dimension Drawing**



