## **NVC Lighting Limited**

NVC Park 201, Hollymoor Way, Rubery, Birmingham, B31 5HE UK **T** +44 (0)121 457 6340 **F** +44 (0)121 453 1325

E sales@nvcuk.com



## DATA SHEET

## **TULSA V4**

Tulsa V4 Digital Dimming Driver 24W 600X600 Panel DC Lead

24W Digital Dimming LED Driver For Panels Plug & Play On Panel Loop In / Loop Out Connector For Ease Of Installation









GENERAL INFORMATION	
Product Code	NTU/DD/DRV/24/66
Product Range	Tulsa V4
Product Category	LED Panels
Fixing Method	Recessed
IP Rating	IP20
IK Rating	N/A
Warranty	5 Years Unlimited Hours
DIMENSION/WEIGHT	
Dimensions (W x H x D) (mm)	N/A
Cut-out Size (mm)	N/A
Product Weight (Kg)	0.3
CONSTRUCTION	
Body Material	N/A
Body Colour	N/A
Optical Material	N/A
Optical Finish	N/A
Termination	5x2x2.5mm sq. Push In Terminal
Driver - Integral or Remote	Remote
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

∠ DC	LEAD	
100		

NTU/DD/DRV/24/66 NTU/DD/DRV/28/66 NTU/DD/DRV/38/66

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (Im)	See Panel
Power Consumption (W)	See Panel
Efficacy (I.Im/c.W)	See Panel
Operating Temp. (Min/Max)	-20°C - 25 °C
LIGHT SOURCE	
Туре	N/A
Correlated Colour Temp.	N/A
Colour Rendering Index (CRI)	N/A
Lumen Depreciation	N/A
SDCM	N/A
ELECTRICAL INPUT	
Voltage (V)	220-240V AC
Operating Frequency	50
In Rush	19A @ 115us
Drivers per MCB*	B10=41 B16=66 C10= 68 C16=111
Class	Class 2
Power Factor	>0.95
Cable Entry	N/A
ELECTRICAL OUTPUT	
Forward Current (mA)	N/A
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	Yes
OTHER	N/A
Switch Dim	Yes
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN Number	5055943086326

<sup>\*</sup> GUIDE ONLY











