


## Indoor light

# RS PRO DL LED 15 W

EAN 4007841007720



## Functional description

Only available from STEINEL. The RS PRO LED DL 15 W LED is the first HF-sensor controlled LED downlighter that can be integrated in the ceiling. But there's not a lot of it you can see. Because once in place, the entire system fits flush with the suspended ceiling. In no time at all, thanks to easy-fit clamp-type retainer. Using interconnected slave versions, RS PRO DL 15 W LED provides even greater energy efficiency.

## Technical specifications

<b>Dimensions (Ø x H)</b>	142.5 x 88 mm
<b>Mains power supply</b>	100 – 240 V , 50 / 60 Hz
<b>Transmitter power</b>	< 1 mW
<b>Output</b>	15 W
<b>Output, detail</b>	Only via Eltako ER12DX-UC with basic light function deactivated
<b>Luminous flux</b>	838 lm
<b>Colour temperature</b>	4000 K
<b>Colour variation LED</b>	SDCM3
<b>Colour Rendering Index CRI</b>	70-79
<b>With lamp</b>	Yes, STEINEL LED system
<b>Lamp</b>	LED cannot be replaced
<b>LED life expectancy (max. °C)</b>	50000 h
<b>Drop in luminous flux in accordance with LM80</b>	L70B10
<b>Base</b>	without
<b>LED cooling system</b>	Passive Thermo Control
<b>With motion detector</b>	No
<b>Photo-cell controller</b>	No
<b>Time setting</b>	60 s – 60 min
<b>Basic light level function time</b>	10 min, 30 min, all night
<b>Impact resistance</b>	IK00
<b>IP rating</b>	IP20
<b>Protection class</b>	II
<b>Ambient temperature</b>	-10 – 40 °C
<b>Housing material</b>	Aluminium
<b>Cover material</b>	Plastic, opal
<b>Manufacturer's Warranty</b>	5 years
<b>Version</b>	Slave - neutral white

Indoor light

# RS PRO DL LED 15 W

EAN 4007841007720

Light distribution curve 1

