

## DATA SHEET


# Arlington

i | | YGIY IO | Y | |  
 | | |  
 G IO | Y | | | | | | |@ | |  
 R IG | | IO | | | | IR | | |  
 R | | | | | Y | |



GENERAL INFORMATION	
Product Code	i
Product Range	i
Product Category	Y
Fixing Method	
IP Rating	
IK Rating	i
Warranty	
DIMENSION/WEIGHT	
Dimensions (W x H x D) (mm)	IG
Cut-out Size (mm)	i
Product Weight (Kg)	
CONSTRUCTION	
Body Material	R
Body Colour	
Optical Material	i
Optical Finish	i
Termination	IO
Driver - Integral or Remote	
PACKAGING	
Carton Dimensions (mm)	i
Quantity per Outer Carton	i
Total Weight incl. Carton (Kg)	i

LUMINAIRE PERFORMANCE	
Energy Rating	i
Luminaire Lumens (lm)	i
Power Consumption (W)	
Efficacy (lm/c.W)	i
Operating Temp. (Min/Max)	R       R
LIGHT SOURCE	
Type	YG
Correlated Colour Temp.	
Colour Rendering Index (CRI)	i
Lumen Depreciation	o
SDCM	i
ELECTRICAL INPUT	
Voltage (V)	iiR
Operating Frequency	
In Rush	i
Drivers per MCB*	i
Class	R
Power Factor	>
Cable Entry	
ELECTRICAL OUTPUT	
Forward Current (mA)	i
Forward Voltage (Vf)	i
EMERGENCY DATA	
Mode of Operation	
Battery Duration	
Battery Type	@
Battery Specification	i
Ballast Lumen Factor (BLF)	i
DIMMING	
DALI	i
OTHER	i
Switch Dim	i
Corridor Function	i
SENSORS	
Microwave	i
PIR	i
STANDARDS/APPROVALS	
CE Marked	
Certificate of Conformity	
Accreditations	i
BARCODE	
EAN Number	



\* GUIDE ONLY