

DATA SHEET

| | | | |
|----------|----------|-----------------------------|-----------------------|
| Item no. | 99909646 | Connector type For cable | F-56 3.9 SELF INSTALL |
| | | | Draka 0,8/3,7 AFB 80% |

Frequency Range

0.3 - 3000 MHz

Impedance (Nom.)

75 Ω

**Amp. Rating (measured)
(calculated)**

Cable data

Transfer Impedance (CoMeT)

<0,9 mΩ/m @ 5-30MHz

Shielding Effectiveness(CoMeT)

<0,02 mΩ/item @ 5-30MHz

>110 dB @ 30-1000MHz

>110 dB @ 1000-3000MHz

All tests performed using instruments calibrated in accordance to our ISO 9001 certification.
 Further technical specifications and installation instructions can be obtained on request.


Return Loss (IEC 61169-1)

(Rhode und Schwarz ZVB-8)

0.3 - 500 MHz

Better than Typical

-38 dB -41,0 dB

500 - 860 MHz

-38 dB -41,0 dB

860 - 1000 MHz

-38 dB -41,0 dB

1000 - 1750 MHz

-38 dB -41,0 dB

1750 - 2150 MHz

-37 dB -40,0 dB

2150 - 3000 MHz

-36 dB -38,7 dB

Insertion Loss Max.
Better than Typical

0.3 - 500 MHz -0,06 dB -0,01 dB

500 - 860 MHz -0,06 dB -0,01 dB

860 - 1000 MHz -0,06 dB -0,01 dB

1000 - 1750 MHz -0,06 dB -0,01 dB

1750 - 2150 MHz -0,06 dB -0,01 dB

2150 - 3000 MHz -0,06 dB -0,01 dB

Temperature

Installing

-5° to +50° C

Operating

-40° to +100° C

Storing

-40° to +100° C

Intermodulation

3rd Order (@2x100mW)

IM3 IP3-value

-145 dBc +92 dBm

Sealing Test

(IEC IP-code)

-

Inner Conductor Resistance

(@ 1 A DC)

Cable data

O-rings

-

Insulation Resistance

(@ 500 VDC)

Cable data

Base Material

Body Parts Brass CuZn39Pb3 / POM(Acetal)

Inner Conductor Cable data

Dielectric Strength

DC Test Voltage

Cable data

Plating

Body Parts Nitin-6

Inner Conductor Cable data

Max. Tensile Strength

Overall

28 Kg.

275 Newton

Insulators

-

Torsional Strength

(Connector / Cable)

* NATM

Remarks

* Not Able To Measure(NATM): The cable starts to twist without the connector loosing its grip.

Distributor:

ISO 9001:2000 / ISO 14001 certified

CABELCON
 connectors

Corning Cabelcon ApS, Industriparken 10, DK 4760 Vordingborg

Tel: +45 55 98 55 99 · Fax: +45 55 98 55 04

E-mail: cabelcon@cabelcon.dk · www.cabelcon.dk