



33 000 002 - 1



DALI-USB interface

DL-USB mini

Only skilled electricians may install this electrical equipment otherwise there is the risk of fire or electric shock!

Temperature at mounting location:
-20°C up to +50°C.
Storage temperature: -25°C up to +70°C.
Relative humidity:
annual average value <75%.

Interface for communication between PC programs and modules in the DALI lighting system. For luminary installation and flush-mounted box. 59 x 33 x 15 mm. Protection class IP20.

Interface module for communication between a DALI system and PC applications.

Bidirectional data traffic.

For addressing, configuration, status queries, parameter settings of DALI components.

Support for DALI standard and various extended DALI protocols.

Monitoring DALI bus communication.

Galvanic isolation. Powered over the DALI bus and the USB interface.

DALI Cockpit PC software to configure and monitor a DALI system.

Double DALI terminals to loop the DALI bus connection.

Technical data

Plug-in terminals:

Max. connection

cross-section

1.5 mm²



The crossed-out waste container indicates that batteries may not be disposed with other household or commercial waste.

Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

Technical Support English:

☎ +49 711 94350025

✉ technical-support@eltako.de

eltako.com

20/2021 Subject to change without notice.